

KNIPEX Quality – Made in Germany



KNIPEX NexStrip® – Multi-Tool for Electricians

3-in-1 combination: Cutting, Stripping & Crimping!

For electrical installation application



KNIPEX NexStrip®

From July 2022

Multi-Tool for Electricians

Wire stripper with three functions: stripping wire up to 10 mm², crimping capacity of 4 mm² or 2 x 2.5 mm² and cutting capacity of 10 mm²

- ▶ Precise stripping: automatically adapts to the respective cable diameter and ensures consistent stripping lengths with the adjustable length stop especially with repetitive work
 - ▶ Perfect crimping: fast and even square crimping for individual wire ferrules, the ratchet crimping mechanism guarantees the required crimping pressure
 - ▶ Multi-component grips ensure non-slip, comfortable handling
- > Quick, precise square crimp of single wire ferrules according to DIN 46228 parts 1+4, self-adjusts for sizes 0.25–4 mm² / 2 x 2.5 mm² – allows for quick crimping between different sizes
 - > Repetitive, high crimping quality due to ratcheting mechanism with a complete crimping cycle
 - > Stripping with fine adjustment – for optimal adjustment to special materials or temperature conditions for flexible and solid conductors between 0.03 and 10 mm² (AWG 32–8)
 - > Cleanly cuts conductors up to 10 mm² (AWG 8)
 - > High-quality housing made of glass fibre reinforced plastic
 - > For the electrical trade: for domestic installations and wiring of electrical devices, such as PLC (programmable logic controller)



With cable cutter for conductors up to 10 mm².




Automatic stripping up to 10 mm².




Square crimping die for wire ferrules of 0.25–4 mm².



The fine adjustment feature allows reliable stripping in all operating conditions like extreme temperatures or special insulating material.



The ratchet crimping mechanism ensures the correct crimping pressure.



Article no.	EAN	↔ mm	Handles	Application	Capacity mm ²	AWG	⚖ g	
12 72 190	N 088165	190	non-slip	Cutting	Cutting up to 10	8	170	
				Stripping	Stripping from 0.03 to 10	32–8		
				Square compression	Crimping of single wire ferrules from 0.25 to 4 Crimping of twin wire ferrules 2 x 2,5			
12 49 21	N 057581		Spare blades block for 12 72 190				8	
12 49 23	N 057604		Spare length stop for 12 72 190					46